

Fogging Oil

SECTION 1. IDENTIFICATION

Product Identifier Fogging Oil
Part number R-6002

Product FamilyPetroleum distillatesRecommended UseEngine storage oil.Restrictions on UseNone known.

Supplier Identifier Revive Products Company, 830 Progress Court, Oakville, ON, L6L 6K1, 1.800.201.9486

Emergency Phone No. CANUTEC, +1.613.996.6666, Operation hours: 24/7

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas; Aspiration hazard - Category 1

Label Elements







Danger

Extremely flammable aerosol.

Pressurized container: may burst if heated.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Do NOT induce vomiting.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Dispose of contents and container in accordance with local, regional, national and international regulations.

% of the mixture consists of an ingredient or ingredients of unknown acute toxicity inhalation.

% of the mixture consists of an ingredient or ingredients of unknown acute toxicity oral.

% of the mixture consists of an ingredient or ingredients of unknown acute toxicity dermal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	40-70	
Petroleum gases, liquefied	68476-85-7	10-30	
Stoddard solvent	8052-41-3	7-13	

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 01 of 07

Calcium sulfonate based corrosion inhibitor	61789-86-4	1-5	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1-5	
Hydrotreated light naphthenic distillate	64742-53-6	1-5	
n-Nonane	111-84-2	0.1-1.0	
Xylene (mixed isomers)	1330-20-7	0.1-1.0	
1,2,4-Trimethylbenzene	95-63-6	0.1-1.0	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice or attention.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Drink two glasses of water. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Immediately call a Poison Centre or doctor.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam. Use water to keep non-leaking, fire-exposed containers cool.

Unsuitable Extinguishing Media

DO NOT use water or water-based extinguishing agents.

Specific Hazards Arising from the Product

Contains gas under pressure; may explode if heated. Closed containers may rupture violently when heated releasing contents. Flammable aerosol. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard. May travel a considerable distance to a source of ignition and flash back to a leak or open container. Pressurized container: May burst if heated.

Very toxic carbon monoxide, carbon dioxide. and other unidentified organic compounds.

Special Protective Equipment and Precautions for Fire-fighters

Use extreme caution. Evacuate area. Fight fire from a safe distance or a protected location.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Eliminate all ignition sources if safe to do so. Distant ignition and flashback are possible. Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Do not

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 02 of 07

allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Contain and soak up spill with absorbent that does not react with spilled product. Contaminated absorbent poses the same hazard as the spilled product. Place used absorbent into suitable, covered, labelled containers for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use. Do not weld, cut or perform hot work on empty container until all traces of product have been removed. Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs.

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated, out of direct sunlight and away from heat and ignition sources. Store at temperatures not exceeding: 40°C.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACG	ACGIH® TLV®		OSHA PEL	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	
n-Nonane	200 ppm	Not established	Not established	Not established	
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	435 mg/m3	Not established	
Stoddard solvent	100 ppm	Not established	Not established	Not established	
1,2,4-Trimethylbenzene	25 ppm	Not established	Not established	Not established	

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Suitable materials are: nitrile rubber, polyvinyl alcohol, Viton®, Barrier® (PE/PA/PE).

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance Dark amber Aerosol.

Odour Petroleum
Odour Threshold Not available
pH Not applicable

Melting Point/Freezing Point Not available (melting)

Initial Boiling Point/Range Not available

Flash Point 40 - 43 °C (closed cup)

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 03 of 07

Evaporation Rate Not available Flammability (solid, gas) Flammable aerosol

Upper/Lower Flammability or

Explosive Limit

Not available (upper); Not available (lower)

Vapour Pressure Not available

Vapour Density (air = 1) > 1

Relative Density (water = 1) 0.833 at 15 °C

Solubility Negligible in water

Partition Coefficient, Not available

n-Octanol/Water (Log Kow)

Auto-ignition TemperatureNot availableDecomposition TemperatureNot available

Viscosity < 14 centistokes at 40°C (kinematic)

Other Information

VOC % Not available
Flame projection > 100 cm
NFPA Classification Aerosol, level 3

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

High temperatures. Elevated pressure.

Incompatible Materials

Strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide. and other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

Likely Routes of Exposure

Skin contact.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
n-Nonane	3200 ppm (rat) (4-hour exposure)	> 15000 mg/kg (rat)	Not available
Xylene (mixed isomers)	6350 ppm (male rat) (4-hour exposure)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)
Calcium sulfonate based corrosion inhibitor	Not available	Not available	Not available

Product Identifier: Fogging Oil

SDS No.: R-6002

Date of Preparation: May 04, 2016

Page 04 of 07

Distillates (petroleum), hydrotreated heavy naphthenic	2180 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Hydrotreated light naphthenic distillate	2180 mg/m3 (rat)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Stoddard solvent	> 5500 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 3000 mg/kg (rabbit)
1,2,4-Trimethylbenzene	18000 mg/m3 (rat) (4-hour exposure)	5000 mg/kg (rat)	Not available

79% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (inhalation).

79% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (oral).

80% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (dermal).

Skin Corrosion/Irritation

There is limited evidence of mild irritation.

Serious Eye Damage/Irritation

There is limited evidence of mild irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

At high concentrations may cause nose and throat irritation, depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Skin Absorption

No information was located.

Ingestion

If large amounts are swallowed can cause effects as described for inhalation. Symptoms may include nausea, vomiting, stomach cramps and diarrhea.

Aspiration Hazard

May cause lung damage if aspirated based on physical properties (e.g. kinematic viscosity) and chemical family (hydrocarbon).

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located for respiratory sensitization.

No information was located for skin sensitization.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Xylene (mixed isomers)	A4	Group 3	Not Listed	Not Listed
Petroleum gases, liquefied	Not Listed	Not Listed	Not Listed	Not Listed

Not a carcinogen.

Key to Abbreviations

ACGIH® = American Conference of Governmental Industrial Hygienists. A4 = Not classifiable as a human carcinogen. IARC = International Agency for Research on Cancer. Group 3 = Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity

Development of Offspring

(Xylene (mixed isomers)) may harm the unborn child.

No information was located for: Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 05 of 07

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Do not reuse empty containers. Empty containers retain product residue. Follow label warnings even if container appears to be empty. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1950	Aerosols	2.1	
US DOT	UN1950	Aerosols	2.1	
IMDG (Marine)	UN1950	Aerosols	2.1	
IATA (Air)	UN1950	Aerosols, flammable	2.1	

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Emergency Response 126 EmS F-D, S-U

Guide No.

Other Information ICAO/IATA PI Y203/203

Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are

met.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL or are not required to be listed.

CEPA - National Pollutant Release Inventory (NPRI)

(Ethylbenzene) Part 1A.

(Xylene (mixed isomers)) Part 1A.

(Stoddard solvent) Part 5.

(Naphthalene) Part 1A.

(1,2,4-Trimethylbenzene) Part 5.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

Additional USA Regulatory Lists

CERCLA. (Ethylbenzene). (Xylene (mixed isomers)). (Naphthalene)

SARA Title III - Section 302: Not applicable.

SARA Title III - Section 313. (Ethylbenzene). (Xylene (mixed isomers)). (Naphthalene). (1,2,4-Trimethylbenzene)

California Proposition 65. (Ethylbenzene). (Naphthalene)

Massachusetts Right To Know: Not applicable.

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 06 of 07

New Jersey Right To Know. (Ethylbenzene). (n-Nonane). (Calcium hydroxide). (Xylene (mixed isomers)). (Petroleum gases, liquefied). (Stoddard solvent). (Naphthalene). (1,2,4-Trimethylbenzene) Pennsylvania Right To Know. (Ethylbenzene). (n-Nonane). (Calcium hydroxide). (Xylene (mixed isomers)). (Petroleum gases, liquefied). (Stoddard solvent). (Naphthalene). (1,2,4-Trimethylbenzene)

SECTION 16. OTHER INFORMATION

NFPA Rating Health - 1 Flammability - 4 Instability - 0

SDS Prepared By Regulatory Compliance

Phone No. 800.201.9486 **Date of Preparation** May 04, 2016

Key to Abbreviations ACGIH® = American Conference of Governmental Hygienists

CANUTEC = Canadian Transport Emergency Centre

CAS = Chemical Abstract Service

CCOHS = Canadian Centre for Occupational Health & Safety

CNS = Central nervous system

GESTIS = GESTIS Substance Database HSDB® = Hazardous Substances Data Bank

IARC = International Agency for Research on Cancer ICAO = International Civil Aviation Organization IMDG = International Maritime Dangerous Goods Code

LC = Lethal concentration

LC = Lethal dose

NFPA = National Fire Protection Association

NTP = National Toxicology Program

OSHA = US Occupational Safety and Health Administration

PPM = Parts per million

RTECS® = Registry of Toxic Effects of Chemical Substances

STEL = Short term exposure limit

TDG = Transportation of Dangerous Goods Regulations (Canada)

TWA = Time weighted average

References Material safety data sheet from manufacturer.

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). HSDB® database. US National Library of Medicine. Available from Canadian Centre for

Occupational Health and Safety (CCOHS).

Registry of Toxic Effects of Chemical Substances (RTECS®) database. Accelrys, Inc. Available from Canadian Centre for Occupational Health and Safety (CCOHS). ECHA - European Chemical Agency, Classification and Labelling Inventory

GESTIS Substance Database

OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

Disclaimer The information contained herein is offered only as a guide to the use and handling of this

specific material and has been prepared in good faith. It is not intended to be all-inclusive, and

the manner and conditions of use and handling may involve other and additional

considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the

use of or reliance on any information contained herein.

Product Identifier: Fogging Oil

SDS No.: R-6002 Page 07 of 07

