

Anchor Cable Ties

- Made from pure nylon
- Impervious to salt, chemical solvents, and acids



Part #	L	Colour	Dia. to	Tensile lbs	Qty
ANC 199200	4"	Natural	13/16"	18	25
ANC 199202	4"	Black	13/16"	18	25
ANC 199246	6"	Natural	1-3/8"	30	25
ANC 199248	6"	Black	1-3/8"	30	25
ANC 199204	8"	Natural	2-3/16"	75	25
ANC 199206	8"	Black	2-3/16"	75	25
ANC 199208	11"	Natural	3"	75	25
ANC 199210	11"	Black	3"	75	25
ANC 199212	14"	Natural	4"	75	25
ANC 199214	14"	Black	4"	75	25
ANC 199259	15"	Black	4"	120	25

Vertex Cable Ties

- Nylon construction
- Operating temp: up to 85°C
- 100/pkg



Part #	Length	Colour	Tensile lbs
VER 81318	4"	Black	18
VER 81322	4"	Black	40
VER 81330	6"	Black	40
VER 81338	8"	Black	50
VER 81342	11"	Black	50
VER 81789	11"	Black	120
VER 81346	14"	Black	50
VER 81350	15"	Black	120

FTZ Cable Ties

- Nylon construction in natural or UV black
- 100/pkg

Part #	L	Colour	Width	Tensile lbs
FTZ 93110	4"	Nat	.10"	18
FTZ 93210	4"	Black	.10"	18
FTZ 93120	5.7"	Nat	.14"	40
FTZ 93220	5.7"	Black	.14"	40
FTZ 93130	8"	Nat	.19"	50
FTZ 93230	8"	Black	.19"	50
FTZ 93150	11.8"	Nat	.19"	50
FTZ 93250	11.8"	Black	.19"	50
FTZ 93160	14.6"	Nat	.19"	50
FTZ 93260	14.6"	Black	.19"	50
FTZ 93270	14.5"	Black	.30"	120

**Pico Cable Ties**

- Pico standard cable ties
- U.V. resistant nylon
- CSA Approved
- Temp Rating: -40°F to 185°F

**White**

Part #	L	W	Tensile lbs	Qty
PIC 7063-C	4"	.085"	18 lbs	100
PIC 7063-PK	4"	.085"	18 lbs	25
PIC 7065-C	5.8"	.135"	30 lbs	100
PIC 7065-PK	5.8"	.135"	30 lbs	25
PIC 7065-M	5.8"	.135"	30 lbs	1000
PIC 7066-C	7.6"	.190"	50 lbs	100
PIC 7066-PK	7.6"	.190"	50 lbs	25
PIC 7066-M	7.6"	.190"	50 lbs	1000
PIC 7066L-PK	8"	.115"	40 lbs	25
PIC 7066L-C	8"	.115"	40 lbs	100
PIC 7067-C	11.1"	.190"	50 lbs	100
PIC 7067-PK	11.1"	.190"	50 lbs	25
PIC 7068-C	14.6"	.190"	50 lbs	100
PIC 7068-PK	14.6"	.190"	50 lbs	25

Black

Part #	L	W	Tensile lbs	Qty
PIC 7063-0-PK	4"	.085"	18 lbs	25
PIC 7063-0-C	4"	.085"	18 lbs	100
PIC 7065-0-PK	5.8"	.135"	30 lbs	25
PIC 7065-0-C	5.8"	.135"	30 lbs	100
PIC 7066-0-PK	7.6"	.190"	50 lbs	25
PIC 7066-0-C	7.6"	.190"	50 lbs	100
PIC 7066-0-M	7.6"	.190"	50 lbs	1000
PIC 7066L-0-C	8"	.115"	40 lbs	100
PIC 7066L-0-PK	8"	.115"	40 lbs	25
PIC 7067-0-PK	11.1"	.190"	50 lbs	25
PIC 7067-0-C	11.1"	.190"	50 lbs	100
PIC 7067-0-M	11.1"	.190"	50 lbs	1000
PIC 7068-0-PK	14.6"	.178"	50 lbs	25
PIC 7068-0-C	14.6"	.178"	50 lbs	100
PIC 7068-0-M	14.6"	.190"	50 lbs	1000

Natural

Part #	L	W	Tensile lbs	Qty
PIC 7069-PK	25.2"	.310"	120 lbs	25

Pico Heavy Duty Cable Ties

Part #	L	W	Tensile lbs	Qty
White				
PIC 7068HD-C	15"	.310"	120 lbs	100
PIC 7068HD-PK	15"	.310"	120 lbs	25
Black				
PIC 7068HD-0-C	15"	.310"	120 lbs	100

Pico Fluorescent Standard Cable Ties

- Packs of 25
- Length: 7.5". Width: .190"
- Loop tensile strength: 50 lbs

PIC 7066N3-PK	Neon green
PIC 7066N4-PK	Neon orange
PIC 7066N7-PK	Neon yellow
PIC 7066N9-PK	Neon pink

**Ancor Self Cutting Cable Ties**

- Integrated self-cutting blade, provides a quick, flush cut
- Made from pure nylon
- 50 lb tensile strength

Part #	L	Colour	Qty
ANC 199334	4"	Natural	500
ANC 199336	4"	Black	50
ANC 199337	4"	Black	500
ANC 199339	6"	Natural	50
ANC 199340	6"	Natural	500
ANC 199342	6"	Black	50
ANC 199343	6"	Black	500
ANC 199274	8"	Natural	20
ANC 199275	8"	Natural	50
ANC 199276	8"	Black	20
ANC 199277	8"	Black	50
ANC 199264	8"	Black	500
ANC 199278	11"	Natural	20
ANC 199279	11"	Natural	50
ANC 199280	11"	Black	20
ANC 199281	11"	Black	50
ANC 199265	11"	Black	500
ANC 199282	14"	Natural	20
ANC 199283	14"	Natural	50
ANC 199284	14"	Black	20
ANC 199285	14"	Black	50
ANC 199266	14"	Black	500

**Ancor HD Self-Cutting Cable Ties**

- Made from pure nylon
- Simply lock and twist to finish the job
- Integrated stainless steel blade leaves a clean flush cut
- 120 lb tensile strength

Part #	L	Colour	Qty
ANC 199318	15	Black	20
ANC 199319	15	Black	100
ANC 199320	15	Natural	20
ANC 199321	15	Natural	100
ANC 199322	17"	Black	10
ANC 199323	17"	Natural	10

**Ancor****Self-Cutting Mounting Cable Ties**

- Made from pure nylon
- Simply lock and twist to finish the job, with no need for additional tools
- Integrated stainless steel blade leaves a clean flush cut
- 50 lb tensile strength



Part #	L	Colour	Qty
ANC 199300	8"	Black	20
ANC 199301	8"	Black	50
ANC 199302	8"	Black	500
ANC 199309	8"	Natural	20
ANC 199310	8"	Natural	50
ANC 199303	11"	Black	20
ANC 199304	11"	Black	50
ANC 199312	11"	Natural	20
ANC 199313	11"	Natural	50
ANC 199306	14"	Black	20
ANC 199307	14"	Black	50
ANC 199315	14"	Natural	20
ANC 199316	14"	Natural	50

Ancor Mounting Cable Ties

- #10 fastener except, heavy duty uses 1/4"



Part #	L	Colour	Dia. to	Tensile lbs	Qty
ANC 199250	6"	Natural	1-3/8"	30	25
ANC 199252	6"	Black	1-3/8"	30	25
ANC 199226	8"	Natural	2"	50	25
ANC 199228	8"	Black	2"	50	25
ANC 199230	14"	Natural	4"	50	25
ANC 199257	14"	Black	4"	50	25
ANC 199258	14"	Black	4"	50	100

FTZ Mounting Head Cable Ties

- Nylon construction in natural or UV black
- 100/pkg

Part #	L	Colour	Width	Tensile lbs
FTZ 93320	5.9"	Nat	.14"	40
FTZ 93420	5.9"	Black	.14"	40

**Vertex Nylon Mounting Cable Ties**

- Nylon construction
- Operating temp: up to 85°C
- 100/pkg

Part #	Length	Colour	Tensile lbs
VER 81765	8"	Black	50
VER 81767	11"	Black	50



Pico Mounting Tab Cable Ties

White

Part #	L	W	Tensile lbs	Mount	Qty
PIC 7071-C	5.8"	.135"	30	# 8	100
PIC 7071-PK	5.8"	.135"	30	# 8	25
PIC 7072-C	8"	.190"	50	#10	100
PIC 7072-PK	8"	.190"	50	#10	25
PIC 7075-C	11.5"	.190"	50	#10	100
PIC 7075-PK	11.5"	.190"	50	#10	25
PIC 7076-C	14.5"	.190"	50	#10	100
PIC 7076-PK	14.5"	.190"	50	#10	25
Heavy Duty					
PIC 7077-PK	15.7"	.310"	120	1/4"	25
PIC 7077K-36	15.7"	.310"	120	1/4"	100

Black

Part #	L	W	Tensile lbs	Mount	Qty
PIC 7071-0-C	5.8"	.135"	30	# 8	100
PIC 7071-0-PK	5.8"	.135"	30	# 8	25
PIC 7072-0-C	8"	.190"	50	#10	100
PIC 7072-0-PK	8"	.190"	50	#10	25
PIC 7075-0-PK	11.5"	.190"	50	#10	25
PIC 7075-0-C	11.5"	.190"	50	#10	100
PIC 7076-0-PK	14.5"	.190"	50	#10	25
PIC 7077-0-PK	15.7"	.310"	120	1/4"	25

Ancor

Low Profile/Hose Cable Ties

- Reduced head height and contour design conforms to the shape of the wire bundle or hose
- Round design and side tail entry creates a round shape optimal for hoses
- Trimmed tail retracts into cavity leaving a clean, low profile installation
- Tamper-proof pawl is inaccessible after installation
- 50 lb tensile strength
- 20/pkg

Part #	L	Colour
ANC 199324	8	Black
ANC 199326	8	Natural
ANC 199328	11	Black
ANC 199330	11	Natural

Pico

Low Profile Cable Tie Clamps

- Reduced head height to standard ties
- Flexible head design for contoured wrapping

PIC 7176-PK	7.5" Natural, 25/pkg
PIC 7176-0-PK	7.5" Black, 25/pkg



Pico

Clamp Style Cable Ties

- Clamp tie has triangular shaped tabs extending beneath the head, allowing for optimal surface contact and complete circumferential compression to 360 degrees
- Recommended for soft rubber hose applications including fuel, water and air vacuum lines
- UV black cable ties are heat stabilized

PIC 7168-0-C 7.5" Black, 100/pkg



Ancor

Cable Tie Assortment Pack

- Black, blue, green, red, white, yellow
- 24 pieces
- Length: 8"

ANC 199224



Sea-Dog

Cable Tie - Mixed Kit

Black UV stabilized nylon In 4", 5-5/8", 8-1/2" and 10-1/2" sizes. Contains 25 of each.

SED 427290-1



Ancor Cable Tie Mounts

- Made from pure virgin nylon 6/6
- Impervious to salt, chemical solvents, and acids
- Screw mount

Part #	Screw Size	Qty/Pkg
ANC 199231	#8	25
ANC 199232	#8	100
ANC 199262	#10	25



Pico Cable Tie Mounts

- Fits Pico cable ties 7063 through 7079

Part #	Mount	Qty	Colour
PIC 7083-34	1/4"	25	Natural
PIC 7083-0-34	1/4"	25	Black
PIC 7083-0-36	1/4"	100	Black
PIC 7084-0-34	#6	25	Black
PIC 7084-0-36	#6	100	Black
PIC 7183-0-36	#8	100	Black
PIC 7183-0-39	#8	1000	Black
PIC 7183-6-34	#8	25	Natural
PIC 7183-6-36	#8	100	Natural
PIC 7183-6-39	#8	1000	Natural



Pico Adhesive Cable Tie Mounts

- Platform with pressure sensitive adhesive backing
- Use with adhesive and screw or adhesive only
- Accommodates cable ties from 4 directions

PIC 7081-C	100/pkg
PIC 7081-PK	25/pkg



Anchor Spiral Wrap

- High-quality black spiral wrap
- UV stable

Part #	Dia	Length
ANC 452251	1/4"	10'
ANC 452381	3/8"	10'
ANC 452501	1/2"	10'
ANC 452505	1/2"	100'
ANC 452751	3/4"	10'

**Pico Spiral Wrap**

- Clear polyethylene expandable spiral cut wrap
- Retains its strength under repeated flexing/binding
- Ends can be secured with tie wraps
- 100' spools

PIC 5120-C	1/4"
PIC 5121-C	3/8"
PIC 5122-C	1/2"

**Anchor Split Loom**

- Black loom protects wires against abrasion

Part #	Size	Length
ANC 453381	3/8"	10'
ANC 453501	1/2"	10'
ANC 453751	3/4"	10'

**Vertex Self Extinguishing Split Loom**

- Rated UL 94-V2 (flame test)

VER 81741	1/4", 50' reel
VER 81742	1/4", 150' reel
VER 81743	1/4", 250' reel
VER 81745	3/8", 50' reel
VER 81746	3/8", 150' reel
VER 81747	3/8", 250' reel
VER 81749	1/2", 50' reel
VER 81750	1/2", 150' reel
VER 81751	1/2", 250' reel
VER 81753	5/8", 50' reel
VER 81754	5/8", 150' reel
VER 81755	5/8", 250' reel
VER 81757	3/4", 50' reel
VER 81759	1", 50' reel
VER 81761	1-1/4", 50' reel
VER 81763	1-1/2", 50' reel

**Pico Convoluted Tubing**

- Flexible black polyethylene tubing
- Excellent protection against abrasion and crushing
- Pre-split for easy insertion of wires, yet the split remains basically closed when the tubing is bent or twisted

PIC 5139-C	5/8" x 100'
PIC 5140-C	1/4" x 100'
PIC 5141-B	3/8" x 50'
PIC 5141-C	3/8" x 100'
PIC 5142-C	1/2" x 100'
PIC 5143-C	3/4" x 100'
PIC 5144-C	1" x 100'

**Shields****Split Wire Conduit Hose**

- Flame retardant polypropylene
- Split longitudinally
- Temperature range: +275°F
- 2" Diameter
- Sold by the foot
- 100' per box

**SHI 128-2"**

► Also See

Techflex pg 198

Pico Heavy Duty Nylon Clamps

- Width: .500"
- Thickness: .060"
- Mounting Hole: .203"



Part #	Diameter		Qty.
	Max.	Min.	
PIC 7118HN-C	1/8"	.115"	100
PIC 7119HN-C	3/16"	.172"	100
PIC 7120HN-C	1/4"	.234"	100
PIC 7121HN-C	5/16"	.297"	100
PIC 7122HN-C	3/8"	.359"	100
PIC 7123HN-C	7/16"	.422"	100
PIC 7124HN-C	1/2"	.484"	100
PIC 7125HN-C	9/16"	.547"	100
PIC 7126HN-C	5/8"	.609"	100
PIC 7126HN-BP	5/8"	.609"	6
PIC 7128HN-C	3/4"	.734"	100
PIC 7128HN-BP	3/4"	.734"	6
PIC 7129HN-C	7/8"	.859"	100
PIC 7129HN-BP	7/8"	.859"	5
PIC 7130HN-BP	1"	.984"	5
PIC 7130HN-C	1"	.984"	100

Pico Light Duty Nylon Clamps

- Width: .375"
- Thickness: .050"
- Mounting Hole: .203"



Part #	Diameter		Qty.
	Max.	Min.	
PIC 7118LN-BP	1/8"	.115"	18
PIC 7119LN-BP	3/16"	.172"	15
PIC 7120LN-BP	1/4"	.234"	14
PIC 7121LN-BP	5/16"	.297"	14
PIC 7122LN-BP	3/8"	.359"	14
PIC 7123LN-BP	7/16"	.422"	14
PIC 7124LN-BP	1/2"	.484"	14

Ancor Cable Nylon Clamps

- Made from nylon for maximum strength
- Resistant to solvents, acids and moisture
- Has unique screw hole to speed up installation
- Black is UV resistant and recommended for outdoor use



Part #	Dia.	Colour	Qty
ANC 401122	1/8"	Natural	25
ANC 401182	3/16"	Natural	25
ANC 401252	1/4"	Natural	25
ANC 401255	1/4"	Natural	100
ANC 402252	1/4"	Black	25
ANC 401312	5/16"	Natural	25
ANC 401372	3/8"	Natural	25
ANC 402372	3/8"	Black	25
ANC 401375	3/8"	Natural	100
ANC 401502	1/2"	Natural	25
ANC 402502	1/2"	Black	25
ANC 401622	5/8"	Natural	25
ANC 401752	3/4"	Natural	25
ANC 402752	3/4"	Black	25
ANC 401892	1"	Natural	25
ANC 401912	1-1/4"	Natural	25
ANC 401932	1-1/2"	Natural	25
ANC 400000	1/8"-1/2"	Assorted	54

Ancor Stainless Steel Insulated Clamps

- 304 Stainless steel for corrosion resistance
- Rubber insulators are temperature, water, fuel, oil, and acid resistant
- Temp rating -40°C to 149°C
- A.B.Y.C. approved



Part #	Dia.	Screw	Pkg
ANC 403182	3/16"	8	10
ANC 403252	1/4"	8	10
ANC 403312	5/16"	8	10
ANC 403372	3/8"	8	10
ANC 403502	1/2"	10	10
ANC 403562	9/16"	10	10
ANC 403622	5/8"	10	10
ANC 403752	3/4"	10	10
ANC 403872	7/8"	10	10
ANC 403892	1"	10	10
ANC 403902	1-1/4"	10	10
ANC 404152	1-1/2"	10	10
ANC 404172	1-3/4"	10	10
ANC 404202	2"	10	10
ANC 404252	2-1/2"	10	10
ANC 404302	3"	10	10

Vertex Stainless Steel Cushion Clamps

- Stainless steel with rubber cushion
- Interior edges are radiused to protect cable insulation
- 10 per package

VER 81423	1/4"
VER 81425	5/16"
VER 81427	3/8"
VER 81429	1/2"
VER 81431	5/8"
VER 81433	3/4"
VER 82010	7/8"
VER 81435	1"
VER 81437	1-1/4"



Pico Rubber Insulated Clamps

- Flexible neoprene cushion holds lines firmly while protecting them from shock, abrasion and vibration
- Aluminum. 1/2" metal width
- 1/4" mount hole

Part #	Size	Quantity
PIC 7314-BP	1/4"	2
PIC 7314-C	1/4"	100
PIC 7314-PK	1/4"	20
PIC 7315-BP	3/8"	2
PIC 7315-C	3/8"	100
PIC 7315-PK	3/8"	20
PIC 7316-BP	1/2"	2
PIC 7316-C	1/2"	100
PIC 7316-PK	1/2"	20
PIC 7317-C	5/8"	100
PIC 7317-PK	5/8"	20
PIC 7318-C	3/4"	100
PIC 7318-PK	3/4"	20
PIC 7318-12	3/4"	2
PIC 7319-C	7/8"	100
PIC 7319-PK	7/8"	17
PIC 7320-C	1"	100
PIC 7320-PK	1"	13
PIC 7321-C	1-1/8"	100
PIC 7321-PK	1-1/8"	10
PIC 7322-C	1-1/4"	100
PIC 7322-PK	1-1/4"	10
PIC 7323-C	1-1/4"	100
PIC 7323-PK	1-1/4"	7
PIC 7324-C	1-1/4"	100
PIC 7324-PK	1-1/4"	5
PIC 7325-C	1-5/8"	100
PIC 7325-PK	1-5/8"	5
PIC 7326-C	1-3/4"	100
PIC 7326-PK	1-3/4"	5
PIC 7327-C	2"	100
PIC 7327-PK	2"	5
PIC 7328-C	2-1/2"	100
PIC 7328-PK	2-1/2"	3





Techflex is a globally recognized specialist in the engineering and manufacture of the most advanced sleeving solutions and related products for the management and protection of wires, cables and hoses.

- Fast installation
- Long length capability
- Extreme flexibility
- Reduced volume
- Light weight
- Quick dissipation of moisture
- Unbeatable great looks

Techflex F6

- A unique split, 10 mil PET semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance
- The lateral split (25% edge overlap) allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners (velcro, tape, etc.)
- F6 will bend to a tight radius without distorting or splitting open and, unlike full rigid tubing, will not impair or affect the flexibility of harnesses
- Allows for the addition or removal of wires without disassembly

TFX F6N0.25BK	1/4" x 100'
TFX F6N0.25BK 200'	1/4" x 200'
TFX F6N0.38BK 150'	3/8" x 150'
TFX F6N0.50BK	1/2" x 75'
TFX F6N0.50BK 150'	1/2" x 150'
TFX F6N0.75BK	3/4" x 50'
TFX F6N1.00BK	1" x 50'
TFX F6N1.50BK	1-1/2" x 25'
TFX F6N2.00BK	2" x 25'

Techflex Installation Tools

This simple tool makes installing long lengths of F6 sleeving a breeze. Just insert your bundle of wires into the shank of the tool and slide it along the split in the sleeving.

TFX INN0.25OR	1/4" sleeve
TFX INN0.50OR	1/2" sleeve
TFX INN0.75OR	3/4" sleeve
TFX INN1.00OR	1" sleeve
TFX INN1.50OR	1-1/2" sleeve



▶ Also See

Hot Knife pg 1033

Techflex Heavy Wall (HW)

- HW is commonly used in industrial and marine applications where extreme abrasion protection is critical
- The durability of HW makes it ideal for protecting hoses and cables that have constant contact with rough and abrasive surfaces
- HW is the perfect solution for use on chains and cables to protect painted or laminated surfaces from scuffing and wear

TFX HWN0.38BK	3/16" - 3/4" x 50'
TFX HWN0.63BK	5/16" - 7/8" x 50'
TFX HWN1.00BK	1/2" - 1-1/2" x 50'
TFX HWN1.50BK	3/4" - 2" x 25'
TFX HWN2.00BK 25	1-1/2 - 3" x 25'
TFX HWN2.00BK	1-1/2 - 3" x 50'



Techflex FLEXPET (PT)

- The unique braided construction and wide expandability allows quick and easy installation over large connectors and long runs
- PT is braided from 10 mil polyethylene terephthalate (PET) monofilament yarns
- The material has a wide operating temperature range, is resistant to chemical degradation, UV radiation, and abrasion
- The sleeving cuts easily and cleanly with a hot knife

TFX PTN0.25BK	1/8" - 7/16" x 100'
TFX PTN0.50BK	1/4" - 3/4" x 100'
TFX PTN0.75BK	1/2" - 1-1/4" x 100'
TFX PTN1.25BK	3/4" - 1-3/4" x 50'
TFX PTN1.50BK	1" - 2-1/8" x 50'
TFX PTN2.00BK	1-1/2 - 3-1/2" x 50'



Techflex Clean Cut

- Same specifications as the PET sleeving with the advantage of being able to cut the material with ordinary scissors and still maintain an extraordinarily fray-resistant end without the addition of chemical binders or adhesives
- Clean Cut's fray resistant properties allows frequent expansion of the cut end without unraveling
- When cut with a hot knife, Clean Cut produces a clean, smooth and virtually frayless end
- Clean Cut is braided for maximum coverage while still allowing enough expansion for easy installation

TFX CCP0.50BK	1/4"-3/4" x 100'
TFX CCP0.75BK	5/8"-1" x 75'
TFX CCP1.00BK	3/4"-1-3/16" x 50'
TFX CCP1.25BK	1"-1-1/2" x 50'
TFX CCP1.50BK	1-1/4"-2" x 50'



Techflex Display Rack

This display/dispenser rack allows easy control of sleeving inventories and provides a controlled system of neatly dispensing directly from the spools. Drop-in replacement for standard spools.

- Wall or counter mountable
- L: 23-1/2" x H: 6" x D: 10"

TFX DSN0.00BK



Shown with product (not included)