

Aqualarm Last Watch II System

Skippers while tired is a hazard to your passengers, to other boaters and to yourself. It works much like an alarm clock: Set the clock up to 99 minutes ahead of time, and if the reset button is not pushed before the time is up, a loud buzzer will sound. If the buzzer is not stopped after 30 seconds, a second alert is sent to a remote audible alarm.



- Works with 12, 24 and 32VDC systems
- 95 dB @ 12VDC
- W: 4.75" x H: 3.25" x D: 2"

AAL 20011

Fireboy/Xintex Diesel Engine Automatic Shutdown System

Compressed gas suppressant will not shutdown a diesel engine. If fire breaks out aboard a diesel-powered vessel, the engine must be shut down immediately. Continued operation may remove the agent creating the possibility of re-ignition. Fireboy engine shutdown systems respond automatically when a Fireboy system discharges. All systems are solid state for greater reliability. The display unit comes with an integrated alarm horn, charged / discharged lights and an override switch for restart or control of auto-shutdown.



*Additional wire harnesses are available for a second station.

FBY ES-3000-01 3 x 10 amp circuits 12V

Fireboy/Xintex Deluxe Discharge Alarm Panel

- 2-3/16" round black bezel
- 68 dBA horn sounds at low pressure or extinguisher discharge
- Reverse polarity protected
- 9-30 VDC, 3-wire connection



FBY DU-RBH-01-R

Fireboy/Xintex Charged/Discharged Panel

- 2-1/2" round plate has adhesive back for easy panel mounting
- Green warning lamp provides constant monitoring of the system
- One comes in each CG and MA systems



FBY 90107

Fireboy Fire Protection

Extinguishant:HFC-227ea (Heptafluoropropane) which is approved for occupied spaces.
 Actuation:.....CG2 systems, direct heat only.
MA2 systems, direct heat and/or mechanical pull cable for manual discharge.
 Limitations:.....DO NOT install a Fireboy rated for less than the total volume of your engine compartment. You may NOT
combine the rated volume of two systems to equal the total volume of your engine compartment.
 Refillability:.....All extinguishers are currently manufactured in refillable cylinders; systems in a fire are not refillable.
 Warranty:One-Year Limited

Fireboy Automatic CG-2 Systems

Coast Guard Approved. They feature an electrically operated control panel lamp and pressure gauge to indicate whether the unit is charged or discharged. Wire required for lamp hook-up to the pressure switch on the cylinder is not included, but stainless steel mounting brackets are. Automatic, heat-activated discharge. One year limited warranty. Diesel powered craft must also install the Automatic Engine Shutdown System or engines may consume the agent before it can extinguish the fire.

Part #	Max. Volume Protected	Actuation Temp.	Diameter	Height	Weight
FBY CG2-075-227-BL	75 cu ft	175°F	4.3"	11.9"	9 lbs
FBY CG2-200-227-BL	200 cu ft	175°F	5.1"	15.5"	17 lbs
FBY CG2-225-227-BL*	225 cu ft	175°F	6.4"	14.7"	26 lbs
FBY CG2-500-227-BL	500 cu ft	175°F	7.2"	24.7"	47 lbs
FBY CG2-700-227-BL*	700 cu ft	175°F	10"	21.6"	64 lbs

* Request Items



Fireboy Manual MA-2 System

Coast Guard Approved. All feature the same electrically operated control panel indicator lamp and pressure gauge as the CG2 series. In addition, they provide optional, manual activation by means of a mechanical pull cable. Cable kits are packaged and sold separately and available in lengths of 6 to 30 feet, in two foot increments. (Longer cable kits available on special order). Primary, heat activation is still automatic. The manual feature is a back up for those who prefer this extra measure of control, or for inspected vessels who are required by USCG regulation. One year limited warranty.

Part #	Max. Volume Protected	Actuation Temp.	Dia.	Height	Weight
FBY MA2-0175-227-BL	175 cu ft	175°F	5.1"	17.2"	21 lbs
FBY MA2-0200-227-BL	200 cu ft	175°F	5.1"	17.2"	22 lbs
FBY MA2-325-227-BL	325 cu ft	175°F	7.1"	17.2"	38 lbs



Parts:
FBY E-4209-06 6' cable assembly
FBY E-4209-16 16' cable assembly
FBY E-4209-20 20' cable assembly

Nortek Alarm Panel



- Combination smoke, fire and bilge alarms
- 12 or 24 VDC operation
- Provisional for dual power sources
- Monitored lines
- Monitored power supply
- Dimmable display
- Audible and visual alarm display
- Latched alarm conditions
- Test button provides the checking of lamp driver circuits, audible indicator and the panel fail/watchdog circuit
- 8" x 4"

NTK ALP504

UL rated type 1-A:10-B:C
Effective against the most common household fires: wood, paper, fabric, flammable liquid fires and live electrical equipment fires

UL rated class 10-B:C
Effective against flammable liquid fires and live electrical equipment fires

UL rated type 5-B:C
Effective against flammable liquid fires and live electrical equipment fires

UL rated class 3-A:40-B:C
Effective against the most common household fires: wood, paper, fabric, flammable liquid fires and live electrical equipment fires

First Alert Fire Spray



This product's portable size makes it ideal for a galley. It's easier to use and discharges four times longer than a regular fire extinguisher, making it effective against common fires. The biodegradable formula is easy to clean up, so you don't have to worry about making a mess indoors.

- Size: 8.2" L x 2.5" W x 9.5" H
- Effective on paper, wood, fabric, cooking oils and electrical fires
- Warranty: 3 years

FIR 1043283

First Alert Dry Chemical Fire Extinguisher



- Durable composite head
- Bracket and strap included
- Chemical resistant & water proof label with 3-step instructions
- **UL rated type 5-B:C**, effective against flammable liquid fires and live electrical equipment fires



Part #	Nominal Capacity	Colour	Dia x L	Weight
FIR FE5R-PWCNA	2.5 lbs	White	3.6" x 12"	4.2 lbs

First Alert Dry Chemical Fire Extinguishers

- Durable metal head - designed to meet demanding needs
- Metal gauge resists corrosion - easy-to-read colour coded gauge provides accurate measurement
- Metal pull pin with safety seal prevents accidental discharging - helps discourage tampering
- Bracket and strap are included for secure placement of extinguisher - easy instructions
- Chemical resistant & water proof label with 4-step instructions won't deteriorate under marine conditions

Part #	Nominal Capacity lbs	U/L Rating	Colour	Dia x Length	Weight
FIR FE1A10GO/WA	2.5	1A-10-B:C	White	3.6" x 14"	4.7 lbs
FIR FE1A10GOA	2.5	1A-10-B:C	Red	3.6" x 14"	4.7 lbs
FIR FE5GO-MNA	2.5	5-B:C	White	3.6" x 12"	4.2 lbs
FIR FE10GO-MNA	2.5	10-B:C	White	3.6" x 14"	4.4 lbs
FIR FE3A40A†	5	3A-40-B:C	Red	6" x 17.4"	9.8 lbs
FIR FEBRA2-6	Small metal mounting bracket 11.75" x 3.9" x 4.2"				
FIR BRACKET-5	Replacement Fire Extinguisher Bracket (up to 5 lbs)				



FE3A40A



†NOTE The FIR FE3A40A comes with a mounting clip, which is not Coast Guard approved. For certification each fire extinguisher must have the appropriate mounting bracket FIR FEBRA5-6 added. (Ordered separately)

SAFETY & NAVIGATION

Fire Extinguishers			
Class A	Class B	Class C	Class D
Solid Fuel Fires	Liquid Fuel Fires	Energized Electrical Fires	Combustible Fires
Wood	Petroleum products	Electric motors	Magnesium
Plastic	Alcohols	Transformers	Titanium
Cloth	Solvents	Appliances	Zirconium
Paper	Paint Product	Distribution panels	Lithium
Rubber			Potassium
Extinguishing Agents			
Water			
Dry chemical	Dry chemical	Dry chemical	Specialized dry powder
Halogen agents	Halogen agents	Halogen agents	
HFC-227ea	HFC-227ea	HFC-227ea	
	Carbon Dioxide (CO2)	Carbon Dioxide (CO2)	